

VersaLat-ST™

KNOTLESS ANCHOR



VERSALAT-ST™

The VersaLat-ST™ is an innovative knotless anchor focused on significantly reducing operation time whilst providing superior pull-out strength. This knotless anchor is designed for ease-of-use and is implanted on it's own or in combination with the VersaTap™ or any of our other medial row/knotted anchors in both large and small-joint repairs in both large and small-joint repairs. Simplicity is what differentiates this anchor from its competitors with surgeons being able to fixate external sutures/suture tapes or ligaments without the need for a pre-drilled/tapped hole. The anchor promotes a single handed insertion technique. The extra suture provided can also be used for the fixation of the biceps tendon or any other ligament fragments.

FEATURES AND BENEFITS

A one-handed technique promotes ease-of-use and decreases operation time

Unique locking mechanism for effective & efficient suture tensioning

Eliminates knots associated with tissue irritation

A retention suture that allows for the fixation of any remaining ligament fragments

Engineered counter thread allows for dependent rotation of the inner shaft upon anchor insertion

Self-punching tip allows for efficient insertion without the need for a pre-tapped hole

Titanium tip adds extra fixation point for increased pull-out strength

Available Sizes:

Item Code	Description	Sizes
ADP008-ST	VersaLat-ST™, PEEK Knotless Anchor	5.5 x 12mm, Self Tapping
ADP016-ST	VersaLat-ST™, PEEK Knotless Anchor	6.5 x 12mm, Self Tapping

MATERIALS & SPECIFICATIONS

Anchor Material: 100% Medical grade Polyether Ether Ketone (PEEK)

Retention Suture Material: One #2 Force Fibre UHMWPE braided suture (non-absorbable)

Introducer: Single-use, cannulated introducer composing of medical grade stainless steel and silicone

Self-Punching Tip: Medical Grade Titanium (Ti-6Al-4V) Tip

EXTENSIVE APPLICATION RANGE

The 5.5mm VersaLat-ST™ to be used as a knotless anchor in single and double-row rotator cuff repair surgery

The 6.5mm VersaLat-ST™ to be used for patients with lower bone integrity

Can be used as a general interference screw or internal brace

References

ADP008-ST	VersaLat, PEEK Knotless Anchor, 5.5 x 12mm, Self-Punching
ADP016-ST	VersaLat, PEEK Knotless Anchor, 6.5 x 12mm, Self-Punching